



Defense Logistics Agency

America's Logistics Combat Support Agency



**The World's Only Eco Safe, Liquid, All Purpose
ABCDK Fire Effective Extinguisher!**



MODEL PFE-101 - 0.4-LITER
NSN#: 4210-01-642-5552
Cage Code: 7B6W1

FIRE RATINGS & LISTINGS (US)
Southwest Research Institute
(SwRI®)
NFPA10 • ANSI/UL711
• Canadian ULC S508 Ratings: 1B,
C, K
"C" Ratings (100kv) Neetrac Lab
Georgia Tech
35kv EN3-7/MPA Dresden

MEASUREMENTS
H: 10" (254 mm)
W: 3" (77.4 mm)

NET FILL WEIGHT
Approx.: 1.1-lbs (0.5Kg.)

FIRE RATINGS & LISTINGS (INTL)
EN3-7: Ratings: 3A, 21B, D,
25F (35kv) Safe



MODEL PFE-103 - 1-LITER
NSN#: 4210-01-642-5556
Cage Code: 7B6W1

FIRE RATINGS & LISTINGS (US)
Southwest Research Institute
(SwRI®)
NFPA10 • ANSI/UL711
• Canadian ULC S508 Ratings: 2B,
C, K
"C" Ratings (100kv) Neetrac Lab
Georgia Tech
35kv EN3-7/MPA Dresden

MEASUREMENTS
H: 16" (405.5-mm)
W: 3" (109 mm)

NET FILL WEIGHT
Approx.: 2.7-lbs (1.8Kg.)

FIRE RATINGS & LISTINGS (INTL)
EN3-7: Ratings: 5A, 55B, D,
40F (35kv) Safe



MODEL PFE-11RS - 1.5-LITER
NSN#: 4210-01-632-9469
Cage Code: 7B6W1

FIRE RATINGS & LISTINGS (US)
Southwest Research Institute
(SwRI®)
NFPA10 • ANSI/UL711
• Canadian ULC S508 Ratings: 5B,
C, K
"C" Ratings (100kv) Neetrac Lab
Georgia Tech
35kv EN3-7/MPA Dresden

MEASUREMENTS
H: 15.5" (405.5-mm)
W: 4.3" (109 mm)

NET FILL WEIGHT
Approx.: 4-lbs (1.8Kg.)

FIRE RATINGS & LISTINGS (INTL)
EN3-7: Ratings: 8A, 89B, D,
75F (35kv) Safe



Model: PFE-101 (0.4-LITER)
ALL FIRE CLASS EFFECTIVE (ABCDK)
UL711 Rated: 1B, C, K



Kidde
2B,C:
\$15.97



Kidde:
711A K
\$19.97



Amerex #B571
Class "D"
\$790.36

**TOTAL COST:
\$826.30**

FOR THE MODELS PFE-103, &PFE-11RS ,THE COMPARATIVE COST WILL EXCEED \$1,000



Tested & Rated at
South West Research Institute

FEATURES:

304 Stainless Steel Micro
Polished for Greater
Corrosion Resistance

Full Cone Fog Spray Nozzle
8 to 10 feet

Operating Temperature:
-30°C to 60°C (-22°F to
140°F) EN3-7

Operating Pressure: US:
200-psi (EN: 15-Bars)

Test Pressure: 600-psi
(41.3 Bars)
Burst Pressure: 2300-psi
(158.5-Bars)

Limited Warranty: 20-year
Onshore & 10-Year for
Offshore Use

SPECIFICATIONS:

FireStopper® PFE-FR FFC
(exclusive to FireStopper®
Branded hardware)

Freeze Resistant to -100°F
(-73.3°C)

• **Eco-Safe**
• Non-Toxic
• Non-Irritant
• Non-Aggressive

All Fire Class Effective
(ABCDK)

Subclass Effective:
• Alcohols • Esters • Ethers
• Carbon Composites
• Rubber • Plastics, etc.

Class "D" Metals:
• Sodium
• Lithium
• Magnesium, etc.

ECO-SAFE (According to OECD 306, PFE-FR meet or exceed
HOCNF, ISO 14669, ISO 5667-16, and ISO 10253 2006,
the FFCs meet "green" qualifying requirements. The FFCs
need no special labeling or chronic health hazard warning
statements and are in compliance with FHSA regulations, 16
CFR 1500 and California Proposition 65)



FIRESTOPPER USA
MASTER DISTRIBUTOR, INC.

FireStopper is a registered trademark of FireStopper International Limited. Used under License. All rights reserved.

4505 Briar Hill West, Lafayette Hill, PA 19444
(215) 262-0972 • email: jvjr@firestopperusa.com
www.firestopperintl.com • cage code: 7B6W1



MADE IN USA